


SURFTEST SJ-310 SERIES

PRE 1383



A portable roughness tester with colour LCD and powerful measurement capability

Mitutoyo

The SurfTest SJ-310 is a Compact, Portable, Easy-to-use Surface Roughness Measurement Instrument Equipped with Extensive Measurement and Analysis Features.



Easy to use

Large colour graphic LCD

The color touch-screen provides excellent readability and an intuitive display that is easy to negotiate. The LCD also includes a backlight for improved visibility in dark environments. The integrated printer allows you to print measurement results on the spot.

Highly functional

Internal memory

Up to 10 measurement conditions and one measured profile can be stored in the internal memory.

Optional memory card

The optional memory card can be used as an extended memory to store large quantities of measured profiles and conditions and adds the convenience of automatically saving data from the 10 most recent measurements.

Password protection

Access to each feature can be password-protected, which prevents unintended operations and allows protection of your settings.

Multilingual support

The display interface supports 16 languages, which can be freely switched. Stylus alarm (patent pending in Japan, U.S.A., EU): An alarm warns you when the cumulative measurement distance exceeds a preset limit.

Extensive analysis and display features

Complies with many industry standards

The SurfTest SJ-310 complies with the following standards: DIN EN ISO, VDA, JIS, ANSI as well as customized settings.

Displays assessed profiles and graphical data

In addition to calculation results, the SurfTest SJ-310 can display sectional calculation results and assessed profiles, load curves, and amplitude distribution curves.

Enhanced power for making measurements on site

Despite its reduced charging time the SurfTest SJ-310 is capable of making approximately 2.5 times the number of measurements when fully charged. The detector supports a variety of measurement orientations and can make measurements up against a wall surface or while facing upward. When combined with optional accessories such as a height gauge adapter, the detector can make measurements in various orientations and settings.



SURFTEST SJ-310

User-friendly, high-functionality display unit with integrated high-speed printer

The large **14,5 cm** (5.7-inch) colour graphic touch-screen LCD provides excellent readability. Furthermore, selecting icons from the touch panel display*1 provides intuitive and easy operation. The integrated high-speed printer also allows the user to perform the entire process from making measurements to printing the results with the push of a single button (START button).

Printer
BAC and ADC curves can be printed in addition to calculation results (including pass/fail results) and assessed profiles. The printer offers an easy-to-understand layout and can also print horizontally to match the content displayed on the LCD. Furthermore, printing speed is approximately 50% faster than conventional models.

14,5 cm color graphic LCD with touch screen

Sheet buttons
Frequently used functions, such as the measurement start button, are provided as rugged sheet buttons with excellent durability.

Built-in battery
With drastically enhanced power compared to conventional models, the SurfTest SJ-310 can make 1500 continuous measurements on a full charge achieved in 4 hours.

Measurement Result Measured profile ↔ One-touch switching ↔ BAC curve ADC curve

PRINT FEED DATA MENU STOP START

*1 Text display can also be selected.


Highly functional detectors and drive units

Detector supplied as standard



One of two types may be selected:

- Measuring force: 0.75 mN
Stylus form: Tip radius 2 µm
Tip angle 60°
- Measuring force: 4 mN
Stylus form: Tip radius 5 µm
Tip angle 90°



A wide range of optional detectors is available, including detectors for small holes, extra small holes, gear tooth surfaces, and deep grooves.

Drive units

Standard drive unit

- Popular standard drive unit



Transverse tracing drive unit

- Best suited for measurement of narrow, shrouded workpiece features such as crankshaft bearings, EDM parts, etc. (Patent registered in Japan)




Retractable drive unit

- The detector is in the retracted position at rest so it is immune from damage when inserted into a feature whose shape cannot be easily seen, such as a blind hole, etc.



Links to a wide variety of external instruments

You can save parameter recalculations and measurement results in text format on a memory card and import into commercial spreadsheet software on a PC. You can also connect to a PC using the USB connector and use a dedicated software application to perform everything from measurement control and condition modification to issuing inspection result reports.




Measurement Assistance and Analysis Features Offering the Ultimate in Ease of Use.

Switches between icon and text display

The display can be switched between icon and text, providing easy, user-friendly operation. Additionally, the guidance feature provides detailed explanations of touch-screen buttons.



Icon





Text




Easy specification of assessment conditions from a list

Setting assessment conditions is simple because you can select the desired condition from a displayed list (e.g., standard, parameter).




Zooming waveforms and analyzing coordinate differences



You can not only magnify or shrink waveforms, but also calculate the coordinate difference between two points using a ruler operation. You can quickly check the irregularity status without waiting for a printout.

Deleting unnecessary data



With the Surftest SJ-310, you can delete portions of measurement data. This feature allows you to make new calculations by deleting data that should not be included in parameter calculation, such as data on a scratch.

Displaying pass/fail results

By specifying a tolerance in advance, you can display pass/fail results in color.



OK




+NG



-NG

Surface texture symbol entry

You can enter assessment conditions using ISO/JIS surface texture symbols. (Patent registered in Japan, U.S.A., Germany, UK, France / Patent pending in China)



Measurement results can be displayed in several ways


Measurement results can be presented in the form of a 1-parameter, profile, 4-parameter or trace display.




1-parameter display:
one parameter measurement result



Profile display: one parameter measurement
result and the measured profile




4-parameter display: four parameter
measurement results



Trace display: the ten latest measurement results
using the same parameter

Recalculation function

After completing measurement, you can modify the assessment conditions (standard, profile, and parameter) and easily recalculate the results using the new condition.* *Not possible with all measurement conditions.





Dual assessment of a single measurement

Using the result of a single measurement, you can make calculations or analyze assessment profiles under two different assessment conditions (standard, profile, filter, etc.) without using the recalculation feature.





Stylus alarm function

The stylus alarm function cumulates the measured lengths, and displays the message when designated threshold value exceeds the cumulative distance.



Positive stylus contact indication

Stylus contact with the workpiece is indicated by color coding in the display. This is helpful when visibility of the surface to be measured is restricted (e.g. when measuring within a shrouded feature or groove).



Extensive statistical processing features

You can make a maximum of 300 statistical measurements using up to three parameters to obtain averages, standard deviations, maximums, minimums, passing rates, and histograms (upper and lower limits can be displayed). This feature is ideal for day-to-day data management.



Specifications

Specifications

Type of detector	Standard drive unit type		Retractable drive unit type		Transverse tracing drive unit		
Model No.	SJ-310 (0.75 mN type)	SJ-310 (4 mN type)	SJ-310 R (0.75 mN type)	SJ-310 R (4 mN type)	SJ-310 S (0.75 mN type)	SJ-310 S (4 mN type)	
Order No.	mm	178-570	178-570	178-572	178-572	178-574	
	inch/mm	178-571	178-571	178-573	178-573	178-575	
Traverse length	X-axis	17.5 mm (.7 inch)				5.6 mm (.22 inch)	
Measuring range	Range	360 μm (-200 μm ~ +160 μm) [14400 μinch (-7900 μinch to +6300 μinch)]					
	Detector	360 μm / 0.02 μm (14400 μinch / .8 μinch)					
Measuring speed	Range/resolution	100 μm / 0.006 μm (4000 μinch / .2 μinch)					
		25 μm / 0.002 μm (1000 μinch / .08 μinch)					
Measuring force / Stylus tip	In the measurement: 0.25 mm/s (.01 inch/s), 0.5 mm/s (.02 inch/s), 0.75 mm/s (.03 inch/s), In the return: 1 mm/s (.04 inch/s)						
Skid force	0.75 mN type: 0.75 mN / 2 μmR 60°, 4 mN type: 4 mN / 5 μmR 90°						
Standard	400 mN or less						
Measured profiles	JIS'82 / JIS'94 / JIS'01 / ISO'97 / ANSI / VDA						
Parameters	Primary, Roughness, DF, R-Motif, W-Motif						
Graph analysis	Ra, Rc, Ry, Rz, Rq, Rt, Rmax ^{*1} , Rp, Rv, R3z, Rsk, Rku, Rc, Rpc, Rsm, Rz1max ^{*2} , S, HSC, RzJIS ^{*3} , Rppi, R Δ a, R Δ q, Rlr, Rmr, Rmr(c), R c, Rk, Rpk, Rvk, Mr1, Mr2, A1, A2, Vo, a, q, L _v , Rpm, tp ^{*4} , Htp ^{*4} , R, Rx, AR, W, AW, Wx, Wte, Possible Customize						
Filter	BAC and ADC curves						
Cut-off length	λ_c	0.08, 0.25, 0.8, 2.5, 8 mm (.003, .01, .03, .1, .3 inch)					
	λ_s ^{*5}	2.5, 8 μm (100, 320 μinch)					
Sampling length	0.08, 0.25, 0.8, 2.5, 8 mm (.003, .01, .03, .1, .3 inch)						
Number of sampling lengths	x1, x2, x3, x4, x5, x6, x7, x8, x9, x10, Arbitrary (0.3 ~ 16.0 mm: 0.01 mm Interval)				x1, x2, x3, x4, x5, x6, x7, x8, x9, x10, Arbitrary (0.3 ~ 5.6 mm: 0.01 mm Interval)		
LCD dimensions	117.8 x 88.2 mm						
Display languages	Japanese, English, German, French, Italian, Spanish, Portuguese, Korean, Traditional Chinese, Simplified Chinese, Czech, Polish, Hungarian Turkish, Swedish, Dutch						
Measurement result display	1-parameter display: one parameter measurement result 4-parameter display: four parameter measurement results Profile display: one parameter measurement result and the measured profile Trace display: The ten latest measurement results using the same parameter						
Printing function	Measurement conditions / Calculation results / GO / NG judgement result / Calculation results for each sampling length / Measurement curve / BAC / ADC / Environmental setting information						
External I/O	USB I/F, Digimatic output, RS-232C I/F, External SW I/F						
Functions	Customization	Desired parameters can be selected for calculation and display					
	GO/NG judgement ^{*6}	Max rule / 16% rule / Average rule / Standard deviation (1 σ , 2 σ , 3 σ)					
	Storage of measurement condition	Save the condition at power OFF					
Storage	Internal memory: Measurement condition (10 sets) Memory card (option): 500 measurement conditions, 10000 measuring data, 10000 text data, 500 statistic data, 1 backup of machine setting, the last ten traces						
Calibration	Auto-calibration with the entry of numerical value / Average calibration with multiple measurement (Max.12 times) is available						
Power-saving	Auto-sleep function (30-600sec) ^{*7}						
Power supply	Two-way power supply: battery (rechargeable Ni-MH battery) and AC adapter Charging time: about 4 hours (may vary due to ambient temperature) Endurance: about 1500 measurements (differs slightly due to use conditions / environment)						
Size (WxDxH)	Display unit	275 x 109 x 198 mm					
	Drive unit	115 x 23 x 26.7 mm					
Mass	About 1.8kg (Display unit + Drive unit + Standard detector)						
Standard accessories	12AAM475 Connecting cable ^{*8}				12AAM475 Connecting cable ^{*8}		
	12AAA217 Nosepiece for plane surface				12AAE643 Point-contact adapter		
12AAA218 Nosepiece for cylinder				12AAE644 V-type adapter			
12AAA216 Supporting leg				12BAK700 Calibration stage			
12BAK700 Calibration stage				12BAG834 Stylus pen			
12BAG834 Stylus pen				12BAL402 Protection sheet			
12BAL402 Protection sheet				270732 Printer paper (5 pieces)			
270732 Printer paper (5 pieces)				12BAL400 Carrying case			
12BAL400 Carrying case				Roughness reference specimen (Ra1 μm), AC adapter, Philips screwdriver, Strap for stylus pen, operation manual, quick reference manual, Warranty			

*1 Only for VDA/ANSI/JIS'82 standards.

*2 Only for ISO '97 standard.

*3 Only for JIS'01 standard.

*4 Only for ANSI standard.

*5 λ_s may not be switchable depending on a standard selected.

*6 Standard deviation only can be selected in ANSI.16% rule cannot be selected in VDA.

*7 Auto-sleep function is invalid when AC adapter is used.

*8 For connecting the calculation display unit and drive unit.

To denote your AC line voltage add the following suffixes (e.g. 178-570-01A).

A for 120V, C for 100V, D for 230V, E for 230V (for UK), DC for 220V (for China), K for 220V (for Korea)


Dimensions

Drive Unit and display unit

Unit: mm

Drive unit type	Drive unit external view
Standard drive unit	<p>Technical drawing of a standard drive unit. It includes a front view showing a circular connector with four pins, a side view showing a cylindrical body with a protruding cable, and a top view showing the unit's profile. Dimensions are: height 23.0, depth 26.0, cable diameter 25.2, cable length 26.7, and total length 115.0.</p>
Retractable drive unit	<p>Technical drawing of a retractable drive unit. It includes a front view showing a circular connector with four pins, a side view showing a cylindrical body with a retractable cable, and a top view showing the unit's profile. Dimensions are: height 23.0, depth 26.0, cable diameter 2.0, cable length 23.2, cable length 26.7, and total length 115.0.</p>
Transverse tracing drive unit	<p>Technical drawing of a transverse tracing drive unit. It includes a front view showing a circular connector with four pins, a side view showing a cylindrical body with a protruding cable, and a top view showing the unit's profile. Dimensions are: height 23.0, depth 26.0, cable diameter 3.0, cable length 6.6, cable length 45.5, cable length 47, and total length 115.0.</p>

Display unit external view




Dimensions

Detectors


Unit: mm

Standard detectors




*Tip radius / Tip angle

Gear-tooth surface detectors




*Tip radius / Tip angle

Small hole detectors




*Tip radius / Tip angle

Deep groove detectors



*Tip radius / Tip angle

Extra small hole detectors



*Tip radius / Tip angle




Accessories

Accessories

Nosepiece for flat surfaces

No.12AAA217

- SJ-310/ 310R standard accessories
- Not available for the transverse tracing drive unit.



Nosepiece for cylindrical surfaces

No.12AAA218


- SJ-310/ 310R standard accessories
- Not available for the transverse tracing drive unit.



V-type adapter

No.12AAE644


- SJ-310S standard accessories
- Dedicated to the transverse tracing drive unit.



Point-contact adapter

No.12AAE643


- SJ-310S standard accessories
- Dedicated to the transverse tracing drive unit.



Extension rod (50 mm)

No.12AAA210

- Not available for the transverse tracing drive unit.



Extension cable (1 m)


No.12BAA303

- For connecting calculation display unit and drive unit.

Support feet set

No.12AAA216


- SJ-310 standard accessory
- Not attachable to the detector side of the transverse tracing drive unit.



Vertical positioning adapter

No.12AAA219


- Not available for the transverse tracing drive unit



Magnetic stand adapter

No.12AAA221 (ø 8 mm)


No.12AAA220 (ø 9.5 mm)



Height gage adapter

No.12AAA222 (9x9 mm)

No.12AAA233 (1/4inx1/2in)



(Note: Not available for the transverse tracing drive unit)

Setting attachments

Enhances measurement efficiency by facilitating the measurement setup of multiple workpieces of the same type and of the hard-to-access sections of a workpiece.

V-type for measuring axially

No.178-033

The V-width is adjustable to the cylindrical workpiece diameter, facilitating axial measurement of a wide range workpiece sizes.

- Adjustable range: ø 5 ~ 150 mm



Slider type

No.178-034

This attachment is ideal for measuring a flat area of a workpiece that has an indentation or step that makes it difficult to attach the drive unit. You can further improve the ease of use by using this attachment with the magnetic installation base (option: No.12AAA910).



Inside diameter type

No.178-035

Greatly facilitates measurement of internal wall surfaces of, for example, a cylinder block.


- Applicable diameter: ø 75 ~ ø 95 mm
- Accessible depth: 30 ~ 135 mm



Optional Accessories: For External Output

Simplified communication program for SURFTEST SJ series

The SurfTest SJ-310 series has a USB interface, enabling data to be transferred to a spreadsheet or other software. We also provide a program that lets you create inspection record tables using a Microsoft Excel® macro.



Required environment*:

- OS:
 - Windows® XP-SP3
 - Windows Vista®
 - Windows® 7
- Spreadsheet software:
 - Microsoft Excel® 2002
 - Microsoft Excel® 2003
 - Microsoft Excel® 2007
 - Microsoft Excel® 2010


The optional USB cable is also required.

- USB cable for SJ-310 series
No.12AAD510

This program can be downloaded free of charge from the Mitutoyo website.
<http://www.mitutoyo.eu>

Contour / Roughness analysis software FORMTRACEPAK

More advanced analysis can be performed by loading SJ-310 series measurement data to software program FORMTRACEPAK via a memory card (option) for processing back at base.



Optional Accessories: For External Equipment

Digimatic mini processor DP-1VR

By connecting this printer to the Surfctest SJ-310's digimatic output, you can print calculation results, perform a variety of statistical analyses, draw a histogram or D chart, and also perform complicated operations for X-R control charts.



SJ-310 DP-1VR Connecting cable
1 m: **No.936937**
2 m: **No.965014**

No.264-504

To denote your AC line voltage add the following suffixes (e.g.264-504-5A).

5A for 120V, 5D for 230V, 5E for 230V (for UK), 5DC for 220V (for China), 5K for 220V (for Korea)

Calculation results input unit INPUT TOOL

This unit allows you to load Surfctest SJ-310 calculation results (SPC output) into commercial spreadsheet software on a PC via a USB connector. You can essentially use a one-touch operation to enter the calculation results (values) into the cells in the spreadsheet software.



USB Input Tool Direct
USB-ITN-D
No.06ADV380D



USB keyboard signal conversion type*
IT-012U
No.264-014-10

*Requires the optional Surfctest SJ-310 connection cable.

1 m: **No.936937**
2 m: **No.965014**

Footswitch

A footswitch is used to trigger measurement. This tool is very useful in cases where you need to measure the same workpiece multiple times using jigs and other fixtures.



No.12AAJ088

Measurement data wireless communication system U-WAVE

This unit allows you to remotely load Surfctest SJ-310 calculation results (SPC output) into commercial spreadsheet software on a PC.

You can essentially use a one-touch operation to enter the calculation results (values) into the cells in the spreadsheet software.



U-WAVE-R
(Connects to the PC)
No.02AZD810D



U-WAVE-T*
(Connects to the SJ-310)
No.02AZD880D

* Requires the optional Surfctest SJ-310 connection cable.

No.02AZD790D

Optional accessories and consumables for SJ-310

- Printer paper (5 rolls) **No.270732**
- Durable printer paper (5 rolls) **No.12AAA876**
- Touch-screen protector sheet (10 sheets) **No.12AAN040**
- Memory card (2GB) * **No.12AAL069**
- Connecting cable (for RS-232C) **No.12AAA882**

*Micro SD card (with a conversion adapter to SD card)

MITUTOYO, DIGIMATIC, SURFTEST and U-WAVE are either registered trademarks or trademarks of Mitutoyo Corp. in Japan and/or other countries/regions. Windows and Windows Vista are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries. Other product, company and brand names mentioned herein are for identification purposes only and may be the trademarks of their respective holders.

Coordinate Measuring Machines	11
Vision Measuring Systems	12
Form Measurement	13
Optical Measuring	14
Sensor Systems	15
Test Equipment and Seismometers	16
Digital Scale and DRO Systems	17
Small Tool Instruments and Data Management	18

Mitutoyo Europe GmbH
Borsigstr. 8-10
41469 Neuss
Germany
T +49 (0) 21 37 -102-0
F +49 (0) 21 37 -102-351
info@mitutoyo.eu
www.mitutoyo.eu

Note: Product illustrations are without obligation. Product descriptions respectively capability characteristics are only binding when explicitly agreed upon.

Mitutoyo